

## JTEXcon Atex



- Scalable housing technology
- Customized assembling of joysticks, push buttons and display
- Graphic display 128 × 64 dots with backlight for indicating HATOX-specific data (signal strength, battery condition, frequency indication, etc.) and data feedback via CAN-bus
- With special Hatox batteries to be used only
- "Listen before talk"-technology with automatic frequency management for higher operational safety
- Several systems can be operated at the same time without disturbing each other

Technical data is subject to change without notice

## General technical data

Temperature range	–20° to +40°C
Type of protection	IP 65 (higher on request)
Housing	Aluminum profile with PA end caps
Technology	Transceiver (bidirectional, half-duplex)
Frequency	433.075–434.775 MHz (69 channels) / Europe / 902–928Mz / USA & CANADA
Output Power	adjustable up to 10 mW
Modulation	FSK
Transmission method	TDMA (Time Division Multiple Access) for Europe
Distance	approx. 300 meters / 1000 feet (depending on environment)
Supply voltage	2.0 .. 4.5 V DC (with 2 special Hatox batteries to be used only)
Power consumption	65 mA @ 2.4 V DC
Weight	depending on type, e.g. version A 1725 g (without batteries)
Batteries	+ 60g
Size	depending on type, e.g. version A 28.5 × 15.5 × 14.0 cm (length × width × height)

Technical data is subject to change without notice